

Amendments to the Claims:

The listing of claims will replace all prior versions, and listings, of claims in the application:

1-13. (Cancelled)

14. (New) A roof extension for a utility vehicle cab, said cab including a left A pillar and a right A pillar in a forward travel direction of the vehicle, at least one rear left pillar, and at least one rear right pillar arranged behind a door cutout in the forward travel direction, the roof extension comprising:

at least two roof bows; and

a roof covering covering said bows,

wherein

a first bow of the at least two roof bows extends from the left A pillar to one of the at least one rear right pillar, and

a second bow of the at least two roof bows extends from the right A pillar to one of the at least one rear left pillar.

15. (New) The roof extension as claimed in claim 14, wherein a right B pillar is one of the at least one rear right pillar and a left B pillar is one of the at least one the rear left pillar.

16. (New) The roof extension as claimed in claim 14, wherein a pillar arranged left of a roof center in the forward travel direction and on a rear wall of the cab is one of the at least one the rear left pillar and a pillar arranged right of the roof center in the forward travel direction and on the rear wall of the cab is one of the at least one the rear right pillar.

17. (New) The roof extension as claimed in claim 14, wherein the first roof bow extends from the left A pillar to a right B pillar and the second roof bow extends from the right A pillar to a left B pillar and in that a third roof bow extends from the left A pillar to a pillar arranged right of the roof center in the forward travel direction on the rear wall of the cab and a fourth roof bow extends from the right A pillar to a pillar arranged left of the roof center in the forward travel direction on the rear wall of the cab.

18. (New) The roof extension as claimed in claim 17, wherein the two roof bows starting from the A pillars are brought together in a region of connection to the A pillar.

19. (New) The roof extension as claimed in claim 18, wherein four roof bows enclose a kite-shaped area, one diagonal of which extends in the travel direction and another other diagonal of which extends transversely to the travel direction.

20. (New) The roof extension as claimed in claim 19, wherein the roof extension comprises a kite-shaped roof opening which is arranged in the kite-shaped area.

21. (New) The roof extension as claimed in claim 14, wherein the roof extension comprises a rectangular roof opening which is aligned approximately parallel to one of the roof bows.

22. (New) The roof extension as claimed in claim 17, wherein a horizontally arranged all-round frame is provided, to which the roof bows are connected.

23. (New) The roof extension as claimed in claim 14, further comprising:
four side parts and a horizontally aligned central part,
wherein each roof bow comprises three portions, the first portion and the third portion of which extend parallel to one of side parts of the roof extension and the second portion of which extends parallel to a central portion of the roof extension.

24. (New) The roof extension as claimed in claim 23, wherein two roof bows extend from respective A pillars, each of said two roof bows extending from their respective A pillar to respective B pillars on opposite sides of the vehicle cab, and said two roof bows intersect in the region of the transition between the

horizontally aligned central part of the roof extension and the side part located at the front of the roof extension in the forward travel direction.

25. (New) The roof extension as claimed in claim 23, wherein two roof bows which extend from respective A pillars, each of said two roof bows extending from their respective A pillars to pillars on opposite sides of the roof center in the travel direction on the rear wall of the cab, and the two roof pillars intersect in a region of a horizontally aligned central part of the roof extension.

26. (New) A cab for a utility vehicle, wherein the cab comprises:

a vehicle cab section; and

a roof extension on the vehicle cab section, said roof extension including a left A pillar and a right A pillar in a forward travel direction of the vehicle, at least one rear left pillar, and at least one rear right pillar arranged behind a door cutout in the forward travel direction, the roof extension comprising:

at least two roof bows; and

a roof covering covering said bows,

wherein

a first bow of the at least two roof bows extends from the left A pillar to one of the at least one rear right pillar, and

a second bow of the at least two roof bows extends from the right A pillar to one of the at least one rear left pillar.